

Technical Data Sheet : TDS 11

SOIL PROBES



(Cut- away sample for visual display only)

The SOIL PROBE pinpoints leaks and identifies the plume of underground VOC contamination . The probes are used in conjunction with the VOC thermal desorption diffusion tube and are positioned in the soil, in a grid pattern over key areas of a site. Organic pollutants migrate through the holes drilled at precise intervals into the hollow steel probe and are retained on a standard diffusive or pumped sorbent tube. This type of screening provides a quick, low cost indication of pollution “hot spots”.

Material : PROBE BODY – Stainless Steel with hardened steel tip.
CAP - Aluminium Alloy fitted with Viton® ‘O’ Rings to prevent ingress of water and Soil debris

Optional Parts : Stainless Steel Mesh to prevent ingress of sand particles in dry sandy areas.
Brass Impact Former to assist in driving probe into soil.

Dimensions : Available in three lengths, 280mm : 430mm : and 880mm
Diameter : 33mm

Contaminated land can be particularly difficult to identify due to the fact that the pollution is often underground and therefore hidden. In addition, pollutants like volatile or semi-volatile organic compounds can move through the soil depending on the hydro-geological nature of the site. The ‘plume’ of pollution may migrate some distance from the original leak or spillage which could have occurred several years or even decades ago.

Oil refineries, chemical plant, waste tips, filling stations and industrial sites in general are all subject to contamination. Derelict industrial land, i.e. “brownfield sites” may also be polluted with organics. The sheer size and number of these sites makes it difficult to assess the level of pollution and monitor its distribution economically.

Ormantine USA offer a cost effective solution for monitoring organics in soil, suitable for both small surveys or larger assessments of industrial sites, the soil probe pinpoints leaks and identifies the plume of underground contamination at minimal cost.

The probes are positioned in the soil, in a grid pattern over key areas of a site. Organic pollutants migrate into the hollow steel probe and are retained on a standard diffusive or pumped sorbent tube. Analysis is by thermal desorption/gas chromatography/mass spectroscopy.

This type of screening provides a quick, low cost indication of pollution “hot spots”.

Technical Data Sheet : TDS 11

SOIL PROBES

The unique cap allows the probe to be suitable for both diffusive and pumped sampling and provides a range of sampling regimes for example :

- Diffusive Monitoring over a 24 hour period
- Pumped monitoring for short time periods
- The connection of two tubes in series to monitor the breakthrough of highly volatile compounds

Some Applications

- Survey Landfill / Commercial Sites Using Grid Sampling
- Pinpoint Undersoil Leakages
- Check sites before and after construction projects to provide evidence of effective land contamination prevention measures
- Track flows of sub-soil pollution
- Draw up detailed contour maps of undersoil pollution
- Carry out pre – diffusive sampling checks using FID or PID

Tubes and Sampling Cap assemblies may be prepared and sealed ready for use in the field where soil probe are already in place

PURCHASE OR HIRE SYSTEM CONTAINING PROBE AND SORBENT TUBE PLUS FULL LABORATORY ANALYSIS AVAILABLE

For further Technical and /or Application Information please contact

Ormantine USA Tel 321 676 7003 Fax 321 676 7699
E-mail sales@ormatineusa.com